

● HARNESS + BELT



**Characteristics**

- Dorsal tied with stainless D eyelet
- Adjustable strap on the legs and shoulder area, four adjustment points
- Adaptable to belt
- EN361 and EN 358 Standards

Description	Reference
Harness 1 dorsal and thoracic mooring	HT-22
Harness 1 dorsal mooring	HT-31
Harness 1 dorsal and 2 thoracic mooring	HT-42
Harness for assembly of electrical lines	HT-
Belt with 2 D lateral mooring - M	Electra
Belt with 2 D lateral mooring - L	CE01-M

● SLINGS



**Characteristics**

- Positioning EN358 sling
- Restriction EN354 Drisse sling
- EN355 sling with Absorber
- Adjustable sling rope
- Nylon rope 11mm / 12mm diameter

Description	Reference
Restriction driss sling	LD11-2-10-10
Positioning sling	LD 11-10-10
Positioning sling with sleeve	LCM 04-4-M40
Reduction positioning sling	LCR 12-2-10-10
Simple rope sling with absorber	LCA 12-2-10-10
Double rope sling with absorber	LCAD 12-2-10-10
Simple rope sling with contrait	LC 12-2-10-10
Double rope sling with contrait	LCF 12-2-10-10-10

● BOOTS AND SHOES



**Characteristics**

- Steel toe
- Steel toe and insole
- Anti-static
- Colors: black and brown
- Sizes: 37-46

Reference
BOTA S1P
SAPATO S1P