

● DIGITAL ISOLATION METER



Characteristics

- Megohms: 20 mohms, 200 mohms, 2000 mohms
- DC Voltage: 250/500/100 volts +/- 10%
- AC Voltage: 0-750 volts +/- 1.5% rdg + 2 dgt
- Impedance: 10m
- Continuities:
 - 0-20 ohms +/- 2% + 4 dgt buzzer;
 - 0-200 ohms +/- 1.5% + 2 dgt buzzer;
 - 0-2 ohms +/- 1.5% + 2 dgt buzzer;
 - (buzzer beeps below 40 ohms. maximum open circuit voltage 3.2 volts, short circuit current 3M)
- Timer: Automatically turns off after about 5 minutes to preserve battery
- Display: 3 1/2 digit LCD 48x52mm
- Dimensions: 163x100x52mm
- Weight: 800 Gr including accessories
- Accessories: Batteries, Probes, tweezers, carrying case, instruction manual.

Reference
ST 2551

● DIGITAL ISOLATION METER



Characteristics

- Controlled by microprocessor
- Megaohms: 0-500000 Mohm
- DC voltage: 0.5 to 40 kv
- Power: 8 1.5-volt batteries
- Dimensions: 330x260x160 mm
- Weight: 3.6 kg
- Accessories: Test leads, batteries and instruction manual

Reference
6212 IN