10. Fuses



Fusíveis | 10.

Features
- Manufactured according to the standards
IEC 269-2-1 and NTC63-210

• 8x31,5



Caliber (Amp)	Un (Volts)	lcc (KA)	Emb (Un)	Ø (mm)	B máx (mm)	Reference
1	400	100	10	8,5	6,7	ZR-00
2	400	100	10	8,5	6,7	ZR-00
4	400	100	10	8,5	6,7	ZR-00
6	400	100	10	8,5	6,7	ZR-00
8	400	100	10	8,5	6,7	ZR-00
10	400	100	10	8,5	6,7	ZR-00
12	400	100	10	8,5	6,7	ZR-00
16	400	100	10	8,5	6,7	ZR-00
20	400	100	10	8,5	6,7	ZR-00
25	400	100	10	8,5	6,7	ZR-00

• 10x38



Caliber (Amp)	Un (Volts)	lcc (KA)	Emb (Un)	Ø (mm)	B máx (mm)	Reference
1	500	100	10	10,3	10,5	ZR-0
2	500	100	10	10,3	10,5	ZR-0
4	500	100	10	10,3	10,5	ZR-0
6	500	100	10	10,3	10,5	ZR-0
8	500	100	10	10,3	10,5	ZR-0
10	500	100	10	10,3	10,5	ZR-0
12	500	100	10	10,3	10,5	ZR-0
16	500	100	10	10,3	10,5	ZR-0
20	500	100	10	10,3	10,5	ZR-0
25	500	100	10	10,3	10,5	ZR-0
32	400	100	10	10,3	10,5	ZR-0

• 14x51



Caliber (Amp)	Un (Volts)	Icc (KA)	Emb (Un)	Ø (mm)	B máx (mm)	Reference
2	690	100	10	14,3	13,8	ZR-1
4	690	100	10	14,3	13,8	ZR-1
6	690	100	10	14,3	13,8	ZR-1
8	690	100	10	14,3	13,8	ZR-1
10	690	100	10	14,3	13,8	ZR-1
12	690	100	10	14,3	13,8	ZR-1
16	690	100	10	14,3	13,8	ZR-1
20	690	100	10	14,3	13,8	ZR-1
25	690	100	10	14,3	13,8	ZR-1
32	690	100	10	14,3	13,8	ZR-1
40	690	100	10	14,3	13,8	ZR-1
50	690	100	10	14,3	13,8	ZR-1

• 22x58



Caliber (Amp)	Un (Volts)	lcc (KA)	Emb (Un)	Ø (mm)	B máx (mm)	Reference
16	690	100	10	22,2	16,2	ZR-2
20	690	100	10	22,2	16,2	ZR-2
25	690	100	10	22,2	16,2	ZR-2
32	690	100	10	22,2	16,2	ZR-2
40	690	100	10	22,2	16,2	ZR-2
50	690	100	10	22,2	16,2	ZR-2
63	690	100	10	22,2	16,2	ZR-2
80	690	100	10	22,2	16,2	ZR-2

• NEUTRAL CARTRIDGES _____

Features

- Cartridges for use in neutral circuits cuts

Designation	Quant.	Туре
8,5 x 31,5	10	ZR-00
10,3 x 38	10	ZR-0
14 x 51	10	ZR-1
22 x 58	10	ZR-2



• KNIFE FUSES

Features

- Fuses high cutting power, manufactured according to the standards : EDU 0636, IEC $\,/$ EN 60 269, DIN 43620

•NH-00 TYPE

Caliber Amp	Un (Volts)	lcc (KA)	Emb (Un)	Reference
4	500	120	3	NH-00
6	500	120	3	NH-00
10	500	120	3	NH-00
16	500	120	3	NH-00
20	500	120	3	NH-00
25	500	120	3	NH-00
32	500	120	3	NH-00
35	500	120	3	NH-00
40	500	120	3	NH-00
63	500	120	3	NH-00
80	500	120	3	NH-00
100	500	120	3	NH-00
125	500	120	3	NH-00
160	500	120	3	NH-00



• NH-1 TYPE

Caliber Amp	Un (Volts)	lcc (KA)	Emb (Un)	Reference
16	500	120	3	NH-1
25	500	120	3	NH-1
32	500	120	3	NH-1
35	500	120	3	NH-1
 40	500	120	3	NH-1
 50	500	120	3	NH-1
63	500	120	3	NH-1
80	500	120	3	NH-1
100	500	120	3	NH-1
125	500	120	3	NH-1
160	500	120	3	NH-1
200	500	120	3	NH-1
250	500	120	3	NH-1
 315	500	120	3	NH-1



. | 10

• NH-2 TYPE



Caliber Amp	Un (Volts)	lcc (KA)	Emb (Un)	Reference
35	500	120	3	NH-2
40	500	120	3	NH-2
50	500	120	3	NH-2
63	500	120	3	NH-2
80	500	120	3	NH-2
100	500	120	3	NH-2
125	500	120	3	NH-2
160	500	120	3	NH-2
200	500	120	3	NH-2
250	500	120	3	NH-2
315	500	120	3	NH-2
355	500	120	3	NH-2
400	500	120	3	NH-2

• NH-3 TYPE



Caliber Amp	Un (Volts)	lcc (KA)	Emb (Un)	Reference
315	500	120	3	NH-3
355	500	120	3	NH-3
400	500	120	3	NH-3
500	500	120	3	NH-3
630	500	120	3	NH-3

• NH-4 TYPE



Caliber Amp	Un (Volts)	Icc (KA)	Emb (Un)	Reference
630	500	120	3	NH-4
800	500	120	3	NH-4
1000	500	120	3	NH-4
1250	500	120	3	NH-4



• NEUTRAL BASES _____

Un (Volts)	In (Amp)	Emb (Un)	Reference			
500	160	3	PP 00N			
	Separador para PK 00e PP 00N					
Base unipolar para neutro amovível						



• NEUTRAL NH KNIFES

Fuses | 10.

In (Amp)	Emb (Un)	Reference
100	5	NV L00
250	5	NV L1
400	5	NV L2
630	5	NV L3
1250	5	NV L4



HANDLE PULLERS

Description	Reference
Handle puller	R00-4
Handle puller	VR 00-4

