

● SERRATED CLAMPS



Features

- The Serrated clamps are available in various types and sizes in natural colors (suffix - 9) or black (suffix - w) suitable for outdoor installation
- Technical features: good weather resistance, heat aging and ultraviolet rays.
- Excellent resistance to all hydrocarbon oils, halogenated organic substances and compounds
- These clamps are not attacked by termites, microorganisms, bacteria or fungi
- SPECIFICATIONS:
- Material: Nylon 6,6 UV Resistance (suffix w)
- Resistance to flame propagation (suffix hs)
- Temperature range: -0 to 85 ° C
- Specifications: MIL -S- 23190-E
- Approvals: QPL ARQUIC

Fixing | 3.

Dimensions (mm)		Ø Admissible (mm)	Load brack (Kg)	Reference
Length	Width			
98	2,5	1,0 - 21	8,2	L-2,5x98
160	2,6	1,0 - 40	8,2	L-2,6x160
200	2,6	1,0 - 52	8,2	L-2,6x200
140	3,6	2,0 - 35	13,6	L-3,6x140
200	3,6	2,0 - 50	13,6	L-3,6x200
290	3,6	2,0 - 80	13,6	L-3,6x290
200	4,8	3,0 - 50	22,7	L-4,8x200
290	4,8	3,5 - 79	22,7	L-4,8x290
360	4,8	3,5 - 103	22,7	L-4,8x360
180	7,8	3,5 - 45	54,4	L-7,8x180
300	7,8	4,0 - 80	54,4	L-7,8x300
365	7,8	8,0 100	54,4	L-7,8x365
540	7,8	35,0 158	54,4	L-7,8x540
750	7,8	35,0 200	54,4	L-7,8x750
780	9,0	32,0 233	71,4	L-9x780
1000	12,5	50,0 302	110,0	L- 12,5x1000

● CLAMPS STAINLESS STEEL - 304



Features

- Clamps stainless steel with high resistance to chemicals, radiation, weathering and high temperatures
- Special closing system for auto-lock allowing an extremely quick and easy installation

Dimensions (mm)		Ø Admissible (mm)	Load brack (N)	Reference
Length	Width			
201	4,6	50	667	KE 1128
259	4,6	69	667	KE 1138
360	4,6	102	667	KE 1148
520	4,6	152	667	KE 1158
201	7,9	50	1112	KE 1328
259	7,9	69	1112	KE 1338
360	7,9	102	1112	KE 1348
520	7,9	152	1112	KE 1358
Tool for application of clamps				K 9229