

● MANUAL HYDRAULIC PRESS

● Y35

Features

- Manual hydraulic press for crimping terminals and connectors in copper wires 10 and the aluminum 400mm² to 300mm² by applying appropriate punches and dies
- Can be used in any position since the pliers head is rotatable by an angle of 180°
- Strength: 12 tons
- Length: Approximately 58cm
- Weight: 6kg
- With the press is provided a portable metal enclosure



● Y39

Features

- With the same functions of Y35. Also spiking terminals, connectors and ferrules second French bimetallic standard, 16-300 mm
- Ferrule used for application of matrices and punches HN.68.D.90 with French standard application of punches adapter (UIADP-3) (NFC 33 090)
- With application adapter (UADP-1) throughout the range of the press Y35 arrays can be applied
- With the press is provided a portable metal enclosure
- The Reference Y39E1P1KE serves to modify a Y35 and turn it into Y39



Reference

Y35
 Y39E1E
 Y39E1P1KE

● MANUAL HYDRAULIC PLIER AND ACCESSORIES

Features

- Hydraulic rotary head pliers crimp terminals and connectors, copper and aluminum pre-insulated with hexagonal compression
- Strength: 52Kn
- Length: Approximately 372mm
- Weight: 2kg



Section mm ²		Reference
Cobre CU	Aluminio AL	
10 a 185	-	Alicate HYCP 185
10 a 16	-	Matriz AHE 1016
25 a 35	16 a 25	Matriz AHE 2535
50 a 70	35 a 50	Matriz AHE 5070
95 a 120	70 a 95	Matriz AHE 95120
150	120	Matriz AHE 120
185	150	Matriz AHE 150
-	185	Matriz AHE 185