

● ALUMINOTHERMIC WELD - ACCESSORIES

● LIGHTER AND FILLING MASS




Reference  
Lighter  
Mass (1kg package)

● CONNECTORS FOR ELECTRODES

**Characteristics**

- Bronze connectors with galvanized screws
- Stainless alternative




Permissible conductors (mm <sup>2</sup> )				maximum radius of the electrode (mm)	Reference
Cable: Min.	Max.	Ø Wire: Min.	Max.		
16	16	4	6	16	KU-16.16
25	25	6	11	(5/8")	KU-16.25
25	25	6	11	16	KU-20.25
70	70	10	13	20	KU-16.63
95	95	10	18	(3/4")	KU-20.12
25	25	6	11	16 e 20	KB-16.25
70	70	10	13	20	KB-16.63
95	95	13	18	16 e 20	KB-20.12

● VARIOUS CONNECTORS - REN TYPE

**Characteristics**

- Bronze connectors with galvanized screws
- Stainless screw alternative, REN type



Permissible conductors (mm <sup>2</sup> )				Thread	Type	Reference
Cable: Min.	Max.	Ø Wire: Min.	Max.			
25	70	6	11	M8x35	-	KBL-25
70	95	11	13	M12x60	-	KBL-63
95	185	13	18	M10x55	-	KBL-125
25	70	6	11	M8x35	'C'	KBL-25I
25	70	6	11	M12x60	'M'	KBL-25S-M12
25	70	11	11	M16x60	'M'	KBL-25S-M16
Cable		Electrode		M10	'E'	KB-16.5I
25	70	16	20			